



# Insect traps

# CAPTURE

Recognised for its fiability, the CAPTURE is suited to service industry environments: retail shops, kitchens, changing rooms, refuse rooms, offices, doctors' and vets' surgeries, analysis laboratories, hotels, reception areas, day nurseries, schools, retirement homes, etc.

## Directions

- For wall mounting: 2 metres above ground-level.
- Position away from light.
- Mount 2 to 3 metres above ground-level between the areas to be protected and the insect entry points.
- Servicing: replace the lamps annually and the glue board every 2 months.
- Pests: flies, mosquitoes, midges, moths, wasps, etc.

## Optional

- Shatterproof lamp.
- Bracket  
(See Accessories on page 45).



- Modern design
- Montage kit and chain supplied
- 360 ° discharge
- Inox 441
- Ferromagnetic ballasts: long-lasting and reliable
- Customisation (12 units or more)

Code	Model	Output			Power supply	Consumption	Application surface area	Electrocution grid voltage	Weight	Dimensions L x H x W	Protection rating	Standard lamp/tube reference	Glue board reference
CAPTURE30i	CAPTURE30 s.steel	2x15W (28cm)	✓		220V / 50Hz	40W max	50m <sup>2</sup>	3700V / 9mA	4kg	33x26x11cm	IP20	TCLE015WS	
CAPTURE300i	CAPTURE300 s.steel	2x15W (43cm)	✓		220V / 50Hz	40W max	80m <sup>2</sup>	3700V / 9mA	5,3kg	48x26x11cm	IP20	T15W	
CAPTURE400i	CAPTURE400 s.steel	2x18W (61cm)	✓		220V / 50Hz	60W max	120m <sup>2</sup>	3700V / 9mA	6,2kg	63,5x26x11cm	IP20	T18W	
CAPTURE800i	CAPTURE 800 s.steel	2x36W (61cm)	✓		220V / 50Hz	100W max	240m <sup>2</sup>	3700V / 9mA	6,9kg	63,5x26x11cm	IP20	T40WS	
CAPTURE30iG	CAPTURE 30 glueboards	2x15W(28cm)		✓	220V / 50Hz	40W max	50m <sup>2</sup>		2,6kg	33x26x12,5cm	IP20	TCLE015WS	PL195x310CN2
CAPTURE300iG	CAPTURE 300 glueboards	2x15W (43cm)		✓	220V / 50Hz	40W max	80m <sup>2</sup>		4,6kg	51x30x16cm	IP20	T15W	PL195x460CN2
CAPTURE400iG	CAPTURE 400 glueboards	2x18W (61cm)		✓	220V / 50Hz	60W max	120m <sup>2</sup>		5,2kg	66,3x30x16cm	IP20	T18W	PL195x610CN2
CAPTURE800iG	CAPTURE 800 glueboards	2x36W (61cm)		✓	220V / 50Hz	100W max	240m <sup>2</sup>		5,5kg	66,3x30x16cm	IP20	T40WS	PL195x610CN2

